

Three Phase Modular Smart Static Energy Meter

M52S



PRODUCT INFORMATION

This Three-Phase CT-Operated Modular Smart Meter is among the latest generation of Three-Phase Smart Meters in the industry.

M52S supports active & reactive energy measurement and instantaneous measurement. With an optional plug-and-play PLC/RF/GPRS communication module, the meter can be used in sophisticated AMI system.

KEY FEATURES

- Full smart functionality
- Bidirectional measurement of instantaneous, energy and demand parameter
- Data logging for instantaneous parameters, billing parameters and block load profile
- Tamper events detection, recording and reporting
- Event logging available with active energy, voltage and current snap shots
- Power fail alerts (last gasp) and power resume information (first breath) available
- Communication options including Optical, RF, PLC & GPRS
- Bidirectional communication with push feature as well as on demand reading
- Remote firmware upgrade
- Net metering feature available
- Prepaid function as per IS 15959 Part-3 (Optional)

Meter Parameters	3 x 240V / 415V	-5(6)A	50Hz	IS 16444 (Part2)
	3P 4W	CL 0.5S		IEC 62056-21
Barcode	39000001			IEC 62053-22
Serial Number				
Made in Singapore	Year of Manufacturing : 2021			



M52S

CLASS 0.5S

THREE PHASE MODULAR SMART STATIC ENERGY METER



SPECIFICATIONS

MEASUREMENT

- Unidirectional or Bidirectional measurement
- Cumulative Energy
- Record Active & Reactive Energy (optional) in Tariffs

INSTANTANEOUS VALUES

- Power, Voltage, Current
- Power Factor, Frequency

DISPLAY

- Large digit LCD display with backlight
- Scrolling display and push button mode configurable
- Display Readable Without Main Power (RWP)
- Tamper and relay status shown as ICON
- Impulse LED available for kWh and kVArh

TARIFF

- Single / TOU
- Up to 8 registers, configurable profiles and seasons

DAILY PROFILE

- Daily profile for 35 days
- Energy

BILLING PROFILE

- Billing profile for 6 months
- Energy, Average PF, Maximum Demand

LOAD PROFILE

- Up to 1 Megabyte of Non-Volatile memory
- Max 35 days storage (30 minutes)
- Up to 16 Channel Load Profile (LP) Programmable
- Energy, Voltage, Current

RTC

- Clock accuracy (daily deviation): $\leq 0.5\text{sec.}$ (23°C)
- RWP (Read Without Power)
- Replaceable Lithium Battery

ANTI-TAMPER

- 4 sealing positions (Terminal & Top Cover)
- Top cover and terminal cover open detection
- Bypass / reverse current
- Neutral missing / neutral disturbance
- Strong magnetic field detection

EVENTS & ALARMS

- Load and Power grid On/Off events detection
- Under Voltage, Over Voltage, Over Current, and Over Load
- Power failure and Power resume
- 200 event records with date and time
- Alarms for events and tampers
- Alarms indication (LED & Buzzer) (optional)

DEMAND MONITORING

- Block / slide mode (optional)
- Demand interval configurable
- Maximum Demand with time stamp
- Historical value (optional)

SECURITY

- Multi-level password for data reading and programming for all available ports
- 2 data access levels (LLS and HLS)
- Encryption of data AES – 128 standard

COMMUNICATION

- Optional port for local communication
- RF / PLC / GPRS Plug and play communication module
- RF module with Wi-Sun Sub GHz transceiver
- PLC with G3-PLC band 150kHz–450kHz
- GPRS support 2G/3G/4G network
- Protocol: DLMS as per IS15959 Part3 Standard
- Push and remote firmware update available
- Prepaid function as per IS15959 Part3 Standard (optional)

M52S

CLASS 0.5S



THREE PHASE MODULAR SMART STATIC ENERGY METER

SPECIFICATIONS

APPLICATION

- CT-Operated Connection

ACCURACY

- Active: Class 0.5
- Reactive: Class 1

NOMINAL VOLTAGE

- 3P4W: 3 x 220V, 3 x 230V, 3 x 240V

CURRENT RANGE

- I_b / I_{ref} : -5A
- I_{max} : 6A, 10A

STARTING CURRENT

- 0.1% I_b & 0.2% I_b

FREQUENCY

- 50Hz / 60Hz

POWER CONSUMPTION

- Voltage Circuit: <2W, <10VA
- Current Circuit: <4VA

TEMPERATURE RANGE

- Operation: -25°C to +55°C
- Storage: -40°C to +70°C
- Limit: -40°C to +70°C

HUMIDITY RANGE

- Up to 95%

PROTECTION DEGREE

- IP 54

EMC

- Electro static discharge
 - Contact discharge: 8kV
 - Air discharge: 15kV
- Fast transient burst: 4kV
- Surge immunity: 4 kV
- Electromagnetic RF Field
 - Frequency range: 80MHz to 2000MHz
 - With voltage: 10V/m
 - Without voltage: 30V/m
- Conducted disturbance
 - Frequency range: 150kHz to 80MHz
 - Voltage level: 10V

INSULATED STRENGTH

- Impulse Voltage: 6kV 1.2/50 μ S
- AC Voltage: 4kV 1 min.

STANDARDS

- IEC 62056-21
- IEC 62053-22
- IS 16444 Part2, IS15959 Part3, IS 14697

DATA STORAGE

- Load Profile: Up to 16 Channels: Voltage, Current and Bidirectional Energy
- Billing Data: 6 billing periods

PHYSICAL DIMENSION

- Dimension: 290mm x 170mm x 85mm
- Weight: Approx. 2 kg.
- Mounting Type: Projection type



Digital MicroSystems Pte Ltd
37 Tannery Lane, #04-08 Tannery House, Singapore 347790
Tel: (65) 6742 1048
Email: commercials@dms-ami.com | Website: www.dms-ami.com

